





API MAKE CASING W SERIES - FLUSH JOINTED



API casing tube is manufactured from cold drawn seamless steel tubing. The dimensions and physical properties are in accordance with ISO 3551-1.1992 and BS4019 Pt.3. 1992. The most stringent quality control measures are employed during the whole manufacturing process. Straightness is controlled to better than 1: 1200.

The W Series Casing is flush jointed and has an integral pin and box thread and is Flush on the outside and the inside. Each length of casing is supplied with one coupling. All casing are normally supplied in length increments of 3 & 1.5 metres or 10ft. & 5ft. Any other length increment may be supplied by request. We can also supply left-hand screwed casing.

ØB

SIZE	L(MTR)	O.D.	I.D.	T.P.I	WEIGHT KGS	PART NUMBERS
AW	1.0	57.10	48.40	4.00	6.20	API-DC-AW-10
AW	1.5	57.10	48.40	4.00	8.30	API-DC-AW-15
AW	3.0	57.10	48.40	4.00	16.90	API-DC-AW-30
BW	1.0	73.00	60.30	4.00	10.60	API-DC-BW-10
BW	1.5	73.00	60.30	4.00	15.30	API-DC-BW-15
BW	3.0	73.00	60.30	4.00	31.20	API-DC-BW-30
NW	1.0	88.90	76.20	4.00	13.20	API-DC-NW-10
NW	1.5	88.90	76.20	4.00	19.10	API-DC-NW-15
NW	3.0	88.90	76.20	4.00	38.80	API-DC-NW-30
HW	1.0	114.30	101.60	4.00	17.40	API-DC-HW-10
HW	1.5	114.30	101.60	4.00	25.00	API-DC-HW-15
HW	3.0	114.30	101.60	4.00	50.80	API-DC-HW-30
HWT	1.0	114.30	101.60	2.50	17.90	API-DC-HWT-10
HWT	1.5	114.30	101.60	2.50	25.00	API-DC-HWT-15
HWT	3.0	114.30	101.60	2.50	509.00	API-DC-HWT-30
PW	1.0	139.70	126.50	3.00	25.00	API-DC-PW-10
PW	1.5	139.70	126.50	3.00	34.70	API-DC-PW-15
PW	3.0	139.70	126.50	3.00	69.40	API-DC-PW-30

- Length may be changed as per customer requirement.
- OD & ID may minorly vary due to availability in market.

