





## API MAKE CASING X SERIES - FLUSH COUPLED





API casing tube is manufactured from cold drawn seamless steel tubing. The dimensions and physical properties are in accordance with ISO 3551-1.1992 and BS4019 Pt.3. 1992. The most stringent quality control measures are employed during the whole manufacturing process. Straightness is controlled to better than 1:1200.

The X Series Casing is flush coupled and has a box thread each end and is connected by means of pin to pin couplings. Each length of casing is supplied with one coupling. All casing are normally supplied in length increments of 3 & 1.5 metres or 10ft. & 5ft. Any other length increment may be supplied by request. We can also supply left-hand screwed casing.

|  |      |        |        | _      |       |            |              |
|--|------|--------|--------|--------|-------|------------|--------------|
| ØA   | SIZE | L(MTR) | O.D.   | I.D.   | T.P.I | WEIGHT KGS | PART NUMBERS |
|  | AX   | 1.0    | 57.40  | 50.80  | 8.00  | 5.20       | API-DC-AX-10 |
|  | AX   | 1.5    | 57.40  | 50.80  | 8.00  | 7.50       | API-DC-AX-15 |
|  | AX   | 3.0    | 57.40  | 50.80  | 8.00  | 14.80      | API-DC-AX-30 |
|  |      |        |        |        |       |            |              |
| Effective Length "L"   | вх   | 1.0    | 73.00  | 60.30  | 8.00  | 10.60      | API-DC-BX-10 |
|  | вх   | 1.5    | 73.00  | 60.30  | 8.00  | 15.30      | API-DC-BX-15 |
|  | вх   | 3.0    | 73.00  | 60.30  | 8.00  | 31.20      | API-DC-BX-30 |
| ig i   |      |        |        |        |       |            |              |
| e Le   | NX   | 1.0    | 88.90  | 76.20  | 8.00  | 13.20      | API-DC-NX-10 |
| ctive  | NX   | 1.5    | 88.90  | 76.20  | 8.00  | 19.10      | API-DC-NX-15 |
| Effe   | NX   | 3.0    | 88.90  | 76.20  | 8.00  | 38.80      | API-DC-NX-30 |
| No.  |      |        |        |        |       |            |              |
|  | НХ   | 1.0    | 114.30 | 101.60 | 5.00  | 17.40      | API-DC-HX-10 |
|  | НХ   | 1.5    | 114.30 | 101.60 | 5.00  | 25.00      | API-DC-HX-15 |
| 3  | НХ   | 3.0    | 114.30 | 101.60 | 5.00  | 50.80      | API-DC-HX-30 |
| AND THE STATE OF T |      |        |        |        |       |            |              |
| 8  |      |        |        |        |       |            |              |
|  |      |        |        |        |       |            |              |
|  |      |        |        |        |       |            |              |
| ØB   |      |        |        |        |       |            |              |
|  |      |        |        |        |       |            |              |

- Length may be changed as per customer requirement.
- OD & ID may minorly vary due to availability in market.

